


no idex
l/pus sup
-uo- size
to p[ilip]

ATTACHMENT



OPERATOR: LEASE NAME:
Millard Deck Gulf State

- 1-3-73 Perforated 5½" casing with LJS at 4073', 4074', 4076', 4091', 4092', 4096', 4097', 4120', 4121', 4124', 4125', 4134', 4138', 4140', 4141', and 4142',
- 1-6-73 Treated perforations from 4073' to 4142' with 1000 gallons 15% NE acid. Swabbed and flowed 50 BWPH.
- 1-9-73 Set CIBP at 3900'. Dumped 2 sacks cement. Perforated 3564' thru 3570', 3575' thru 3578', 3610' thru 3620', 3670 thru 3673', and 3677' thru 3681'. Treated perforations with 2000 gallons 15% NE acid. Frac with 60,000 gallons gelled brine and 120,000# of sand.
- 1-10-73 Perforations from 3564' thru 3681' swabbed and flowed 30 BFPH, 2% oil.
- 1-22-73 Set RBP at 3050'.
Perforated 2862' thru 2865', 2876' thru 2884', and 2898' thru 2905'.
- Treated perforations with 1000 gallons 15% NE acid.
- 1-23-73 Fracture treat perforations using 40,000 gallons gelled brine with 40,000# of sand.
- 1-24-73 Open up - flowing 800 BPD, 100% water. SI