

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator Atlantic Richfield Company		8. Farm or Lease Name W.B. Guthrie WN
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201		9. Well No. 2
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 34 TOWNSHIP 23-S RANGE 36-E NMPM.		10. Field and Pool, or Wildcat Jalmat-Yates
15. Elevation (Show whether DF, RT, GR, etc.) 3389' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input checked="" type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input checked="" type="checkbox"/>	OTHER	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Leatherwood Drilling Company spudded 12¼" hole @ 11:00 AM 3/20/73. Drld 12¼" hole to 430'. Ran 13 jts (413.04') 8-5/8" OD 8R 24# J-55 ST&C casing w/guide shoe and float collar, set @ 428.57'. Cemented w/300 sx Class C cement containing 2% CaCl & 1/4#/sk Flocele. Plug down @ 11:00 PM 3/20/73. After 20½ hrs tested casing to 800# for 30 min, OK. Resumed drilling 7-7/8" hole @ 7:30 PM 3/21/73. Circulated 20 sx cement to pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. D. Butcher</u>	TITLE <u>Dist. Drlg. Supervisor</u>	DATE <u>3/23/73</u>
APPROVED BY <u>[Signature]</u>	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		