

| CLASS                     |       | ELEV.     |       | L & S |  |
|---------------------------|-------|-----------|-------|-------|--|
| FORMATION                 | DATUM | FORMATION | DATUM |       |  |
| SPD 3-20-73 CMP 5-20-73   |       |           |       |       |  |
| CSG                       |       |           |       |       |  |
| 13 3/8" at 1225' w/800 sx |       |           |       |       |  |
| 5 1/2" at 8910' w/500 sx  |       |           |       |       |  |
|                           |       |           |       |       |  |
|                           |       |           |       |       |  |
|                           |       |           |       |       |  |
|                           |       |           |       |       |  |
| TD 8910'                  |       | PBD 8868' |       |       |  |

|       |              |           |       |    |    |       |      |    |
|-------|--------------|-----------|-------|----|----|-------|------|----|
| CONTR | Marcum Drlg. | OPRS ELEV | 3613' | DF | PD | 8900' | TYPE | RT |
|-------|--------------|-----------|-------|----|----|-------|------|----|

F.R. 3-26-73  
(Bone Spring)  
3-21-73 Drlg 463' anhy  
3-26-73 TD 1450'; Fshg DC  
4-3-73 Drlg 5070'  
4-10-73 Drlg 7650'  
4-17-73 Drlg 8547'  
4-24-73 TD 8910'; PBD 8868'; WOCU  
5-1-73 TD 8910'; PBD 8868'; Swbg  
Perf @ 8675', 8688', 8698', 8710', 8721',  
8733', 8746', 8766' w/2 SPI  
Acid (8675-8766') 7500 gals (28%)  
Swbd dry  
Acid (8675-8766') 3000 gals (15% MA)  
Frac (8675-8766') 15,000 gals gel wtr + 20,000# sd  
5-8-73 TD 8910'; PBD 8868'; ST  
7-2-73 TD 8910'; PBD 8868'; ST

LEA  
CONTINENTAL OIL CO.

Bell Lake NM Sec 6, T24S, R34E  
13x Bell Lake Unit Page #2

7-9-73

TD 8910': PBD 8868'; TEMPORARILY ABANDONED  
Swbd 14 BF (5% oil) in 4 hrs  
(8675-8766')

7-14-73

LOG TOPS: Anhydrite 1205', Salt 1446', Delaware  
Sand 5162', Bone Spring 8669'  
COMPLETION REPORTED