

[illegible]

(Delaware) Perfs 4964-77' SHUT IN GAS WELL

CONTR	360005	OPRS ELEV	3597' GL	PD	5070	TYPE	R
-------	--------	-----------	----------	----	------	------	---

P.R. 5-28-73
 (Delaware)
 5-3-73 TD 1200'; WOG
 5-4-73 Drig 4580' 1m
 5-5-73 TD 5038'; Tstg
 Corrd 4161-5011', rec 50' mud w/29' sd
 Perf 4964-66', 4968-70', 4973-75', 4977'
 Acid (4964-4977') 500 gals
 Frac (4964-4977') 10,000 gals wrt + 20,000# sd
 Flwd 15 BO in 3 hrs thru 18/64" cnk, FIP 600-700#
 5-14-73 TD 5038'; Flwg Ld
 Flwd 3 BO + 950 MCFGPD in 24 hrs thru 12/64" cnk
 5-26-73 TD 5038'; SI
 Flwd 58 BHO + 32 BW + 1200 MCFGPD in 48 hrs thru
 16/64" cnk

IEA
CONTINENTAL OIL CO.

Undesignated
1 Wimberly "12"
Sec 12, T24S, R32E

NM
Page #2

 TD 5038'; SI
~~9-18-73~~ TD 5038'; SI
9-26-73 TD 5038'; SI
10-4-73 TD 5038'; SI
12-11-73 TD 5038'; WO Pot
Flow 516 MCFGPD in 24 hrs, 14/64" chk, GOF
129,000; FIP 900#
12-11-73 TD 5038'; WO Four Point Gauges
3-11-74 TD 5038'; COMPLETE
Flow 1100 MCFGPD + 10 BW thru 14/64" chk, FTP
1400#, CF 1500#, GOR 129,000
LOG TOPS: Base Salt 4673', Lamar 4916',
Delaware 4960', Ford 5000'
3-16-74 COMPLETION REPORTED
