

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

1625 French Dr.

10556, NM 88240

FORM APPROVED

Reg Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil

Gas



Well



Well



Other

2. Name of Operator

Primal Energy Corporation

3. Address and Telephone No.

211 Highland Cross, Suite #227, Houston TX 77073

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 1,980' FNL & 660' FEL, Sec. 12, T24S, R32E

5. Lease Designation and Serial No.

NM02889

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Wimberly #3

9. API Well No.

30-025-24468

10. Field and Pool, or Exploratory Area

Triple X Delaware

11. County or Parish, State

Lea, NM

12. **CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION



Notice of Intent



Subsequent Report



Final Abandonment Notice

TYPE OF ACTION



Abandonment



Recompletion



Plugging Back



Casing Repair



Altering Casing



Other



Change of Plans



New Construction



Non-Routine Fracturing



Water Shut-Off



Conversion to Injection



Dispose Water

(Note: Report results of multiple completion on Well

Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.
If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. CIBP set at 4,901' in June, 2000. Circulate hole with mud. Set cement plug with 45 sx from 4,901' to 4,522'.

2. Cut and pull 5 1/2" casing below salt at 1,400'. Set plug 50' in and 50' out of casing stub. Tag plug.

3. Set 70 sx plug from 1,382' to 1,282'. Set 50 sx surface plug. Erect dry hole marker. Clean and restore location.

4. 25 sx minimum shoe plug, balanced over shoe at 442 ft and TAG.

5. Surface Plug

APPROVED FOR 3 MONTH PERIOD
ENDING 7/02/02

14. I hereby certify that the foregoing is true and correct

Signed

Title Manager, Operations and Engineering

Date 03/19/02

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of Approval, if any:

Title 18 U.S.C. Section 101, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

See Instructions On Reverse Side

GW

RECEIVED

2002 MAR 26 AM 9:04

BURTON, JOHN RAY

2002 MAR 22 PM 1:40

2002 MAR 22