

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1200'	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1276'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 2504'	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2640'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2790'	T. Devonian	T. Menefee	T. Madison
T. Queen 3178'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1200'	1276'	76'	Anhydrite				
1276'	2504'	1228'	Salt w/Anhydrite Stringers				
2504'	2640'	136'	Sdy. Dolomite and Anhydrite				
2640'	2790'	150'	Dolomite w/Sand Stringers (Yates)				
2790'	3178'	388'	Dolomite, Anhydrite, and Sand Stringers (Seven Rivers)				
3178'	3584'	406'	Sdy. Dolomite, Anhydrite, and Sand Stringers (Queen)				
3584'	3750'	166'	Sdy. Dolomite w/Sand Stringers (Penrose Sand)				
Item 32							
3593-3600'			Squeezed original perms. w/100 bbls. Injectrol followed w/50 sxs. Class C cement w/1% CFR-2 and 50 sxs. Class C cement w/1% CFR-2 and 10# sand per sx. after testing nearly 100% wtr.				
3593-3600'			Re-treated after squeeze w/1,450 gals. 15% acid and fracture treated w/13,000 gals. gelled brine wtr. and 10,000# sand.				