Form 9-331 (May 1963)

TEST WATER SHUT-OFF

FRACTURE TREAT

REPAIR WELL

SHOOT OR ACIDIZE

UNITED STATES DEPARTMENT F THE INTERIOR (Other instructions of verse side) GEOLOGICAL SURVEY

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

NM-0535585 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY	NOTICES	AND	REPORTS	ON W	/ELLS
use this form	for proposals to	drill or to	deepen or plug	g back to a	different

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

REPAIRING WELL

ALTERING CASING

ABANDON MENT*

SURFACE CASING

16.	Check Appropriate Box To Indicate Nature of Notice, Restrict of Intention to:	Report, or Other Data SUBSEQUENT REPORT OF:
	2958.2' GR	LEA NEW MEXICO
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
1980' FSL 8	% 990' FEL	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 29-T26S-R38E
4. LOCATION OF WELL (Re See also space 17 below At surface	eport location clearly and in accordance with any State requirements.* w.)	10. FIELD AND POOL, OR WILDCAT WILDCAT
	348, Roswell, New Mexico 88201	1
	JIL CORFORATION	9. WELL NO.
2. NAME OF OPERATOR	DIL CORPORATION	TIP FEDERAL
OIL K GAS WELL	OTHER	S. FARM OR LEASE NAME
(170 not use tais 1	Use "APPLICATION FOR PERMIT—" for such proposals.)	7. UNIT AGREEMENT NAME
	form for proposals to drill or to deepen or plug back to a different rese	rvoir.

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

XX

WATER SHUT-OFF

FRACTURE TREATMENT

(Other)

ON APRIL 3 RAN 317' OF USED, 24#, 8-5/8" CASING AT 317, CEMENTED WITH 175 SACKS CLASS "C" CEMENT, 2% CALCIUM CHLORIDE, CIRCULATED 50 SACKS. PLUG DOWN 10:15 A. M. APRIL 4. WOC 18 HOURS. HALLIBURTON PRESSURED UP TO 500# TO TEST. NO DROP IN PRESSURE. DRILLED OUT CEMENT PLUG AND RESUMED DRILLING.

THIS TEST WAS ORIGINALLY FILED AS A 3000' TEST OF THE YATES FORMATION. IT IS NOW PLANNED TO TAKE THIS TEST TO AN APPROXIMATE DEPTH OF 4000' TO TEST THE QUEEN FORMATION.

18. I hereby certify that the foregoing is true and correct SIGNED Jack L. Mus Chellager	Æ	OPERATOR	00 10000	DATE _	April	5,	197 [[]
(This space for Federal or State office use) APPROVED BY	rle	NOST TO	13.7 O	PATE	,		
*See In	structions or	Reverse Side)			