

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other P&A  
well well
2. NAME OF OPERATOR  
Conoco Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

## SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

5. LEASE  
LC-061374 A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Bell Lake Unit
8. FARM OR LEASE NAME  
Bell Lake Unit 5
9. WELL NO.  
116
10. FIELD OR WILDCAT NAME  
Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 7, T-24S, R-34E
12. COUNTY OR PARISH Lea 13. STATE N.M.
14. API NO.  
30-025-24910
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3599'

(NOTE) Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU 12-18-79. POOH w/ tbg. & pkr. Set cmt. retainer @ 9035'.  
Tested csq. - held pressure. Pumped 190 sx. class "C" cmt. below  
retainer & 10 sx. on top of retainer. Spotted 45 sx. class "C" cmt.  
@ 5268'. Found csq. free pt. @ 3800'. Shot 7 5/8" csq. @ 3281'.  
POOH w/ 79 jts. 7 5/8" OD, 34", buttress csq. Set 50 sx class "C"  
cmt. @ 3356'. Set 90 sx. class "C" cmt @ 1300'. Set 25  
sx. class "C" cmt. from 50' to surface. Erect P&A marker 12-29-79.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butts TITLE Admin. Supervisor DATE 11/3/80(Orig. Sgd.) GEORGE H. JAWA (Title for Federal or State office use)APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

4565-5  
BASS  
B.M. Lowe  
Phillips

TITLE DISTRICT ENGINEER DATE SEP 18 1980

7M

2000

2000

RECEIVED

SEP 30 1980

U.S. CONSERVATION DIV