

(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form No. 10-11-1

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <b>Dry</b>		5. LEASE DESIGNATION AND SERIAL NO. <b>NM 7951</b>	
2. NAME OF OPERATOR <b>Union Texas Petroleum Corporation</b>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR <b>1300 Wilco Building, Midland, Texas 79701</b>		7. UNIT AGREEMENT NAME <b>Leonard <del>Federal</del> "14" Federal</b>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space below.) At surface  <b>Unit Letter "O" 660' FSL &amp; 1980' FEL</b>		8. FARM OR LEASE NAME	
14. PERMIT NO.		9. WELL NO. <b>1</b>	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <b>2,989.4 GL</b>		10. FIELD AND POOL, OR WILDCAT <b>Wildcat</b>	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <b>Sec. 14, T-26-S, R-37-E</b>	
		12. COUNTY OR PARISH <b>Lea</b>	13. STATE <b>New Mexico</b>

### 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

**Plug & Abandon** ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

### 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. January 11, 1976, T.D. 10,650', displaced hole with 9.3# mud laden fluid.
2. Spotted 50 Sx. plug from 10,460' to 10,330'.
3. Spotted 50 Sx. plug from 9,300' to 9,170'.
4. Spotted 50 Sx. plug from 7,450' to 7,320'.
5. Spotted 50 Sx. plug from 5,300' to 5,170'.
6. Spotted 50 Sx. plug from 3,950' to 3,820'.
7. Spotted 50 Sx. plug from 2,700' to 2,570'.
8. Spotted 50 Sx. plug from 1,100' to 970'.
9. Removed casing head and spotted 10 Sx. plug at surface.
10. Welded 1/2" steel plate into top of 13-3/8" casing and installed dry hole marker.
11. Completed plugging well January 12, 1976.

NOTE: Virbal approval to plug this well was given January 10, 1976, by Mr. Brown at USGS office in Hobbs, New Mexico.

### 18. I hereby certify that the foregoing is true and correct

SIGNED Stanley A. Post

TITLE Gas Measurement Analyst

DATE January 14, 1976

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side