

DA&S OIL WELL SERVICING

INCORPORATED

Lewis B. Burleson, Inc.
Dale Federal No. 1

- 9/16/94 Move in, rig up, put on BOP, pull tubing out, shut down.
- 9/19/94 Run casing scraper to 3000', pull out, run cast iron bridge plug, set at 3000', circulate mud, spot 15 sacks, pull tubing out, perf well at 2300', try to pump outside $4\frac{1}{2}$, pressure up to 500lb., run tubing to 2350', spot 25 sacks, pull tubing, shut down.
- 9/20/94 Tag cement at 2000', plug from 2350' - 2000', perf well at 1100, good circulation, pump 20 sacks outside $4\frac{1}{2}$ casing, 20 sacks inside $4\frac{1}{2}$, wait 4 hours, tag cement at 800', perf well at 700', circulate cement down $4\frac{1}{2}$ to 700 up 8 5/8 to surface with 150 sacks, shut down.
- 9/21/94 Cut off wellhead, put in marker, rig down, move off.

Class "C" Cement
Mud - 25 lb. Salt Gel per bbl.

Ok by Pat at B.L.M.

505-392-6591 • P.O. BOX 2545 • HOBBS, NEW MEXICO 88241

HOBBS, NEW MEXICO (505) 392-6591
ANDREWS, TEXAS (915) 523-4420

LOCATIONS

EUNICE, NEW MEXICO (505) 394-2557
MIDLAND, TEXAS (915) 685-8555