

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

Box 460 Hobbs, N.M. 78240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL, 1980' FWL.

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other)

5. LEASE

NMO 2889

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

WIMBERLY

9. WELL NO.

8

10. FIELD OR WILDCAT NAME

DOUBLE X DELAWARE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 12, T-24S, R-32E

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3593 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

AUG 2 1978

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

IT IS PROPOSED TO PIA THE SUBJECT WELL AS FOLLOWS:

- RIG UP & KILL WELL.
- PULL PROD. Tbg., and set CMT. RETAINER AT 4900'
- SQUEEZE 50 SX CLASS "C" CMT BELOW RETAINER.
- SPOT 50 SX CLASS "C" CMT FROM 4900' TO 4600'.
- DISPLACE FLUID IN CCG W/SALT MUD [32 SX BEUTONITE GEL MIXED W/ 125 bbls brine wtr]
- TEST FOR FREE PT., BLAST & UNSCREW 5 1/2 cgs at FREEPOINT - [TOP OF CMT. 3070' BY TEMP. SURVEY]
- SPOT 50 SX CLASS "C" CMT FROM 80' BELOW TO 80' ABOVE TOP OF 5 1/2" CCG.
- SPOT 80 SX CLASS "C" CMT FROM 1400' TO 1175'
- SPOT 50 SX CLASS "C" CMT FROM 100' TO SURFACE
- ERECT DRY HOLE MARKER, WELD ON METAL CAP, CLEAN LOCATION.

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butterfield

TITLE ADMIN. SUPV

DATE 7-31-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
AS AMENDED

AUG 2 1978

R. O. L.

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

49GS [5], FILE

037
00000000

RECEIVED

AUG 8 1978

COMMUNICATIONS
SECTION
FBI