

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 02 889	
2. NAME OF OPERATOR Continental Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 460, Hobbs, N. Mexico		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 1980' FWL of Sec. 12		8. FARM OR LEASE NAME Wimberly	
14. PERMIT NO.		9. WELL NO. 8	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3593' GR		10. FIELD AND POOL, OR WILDCAT Double X Delaware	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 12, T-24S, R-32E	
		12. COUNTY OR PARISH LEA	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 6:00pm, 6-4-77. Drilled 12 1/4" hole to 1248'. Set 31 joints 8 5/8", 24", K-55, STVC casing at 1248' with 350sx class "c" cmt w/ 4% gel, 2% CaCl₂. 2nd stage w/ 300sx class "c" cmt w/ 2% CaCl₂ and 1/4# / sk floccle. Plug down at 8:15 pm. Circulate approximately 150 sx cmt. Drilled ahead with 7 7/8" hole.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Butts

TITLE

ADMIN. SUPR

DATE

6-8-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

JUN 9 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

USGS(5), File(2)

RECEIVED

JUN 14 1977

U.S. DEPT. OF COMMERCE
WASHINGTON, D.C.