

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
A	35' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	High density wet process porcelain pin insulator		463		
D	5/8" x 5" Forged steel pin w/sq. washer, nut, & locknut	881			
E	5/8" x 12" machine bolt w/ nut (or length req'd)	8812			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	6813			
G	3/8" wt locknut	3512			
H	Wooden CROSS ARM BRACES	7128			
J	1/2" x 4" E7 Better Drive Log Screw	508754			
K	3/8" x 4 1/2" carriage Bolt w/ nut	8634 1/2			
L	3/8" wt locknut	3510			
M	Preforced Aluminum Alloy Armor Rods, size req'd				
N	tie wire #6 strong alum. alloy				
O					
P	35' class 5 creosoted pine pole				
R	Aluminum double tab Squeeze on Connector for ACSS, Aluminum, or Copper-alloy req'd			KEARNEY SERIES "RI"	X
S	6" Suspension Insulator	66700			
T	5/8" Standard Oval Eye Nut	6502			
U	Primary Thread End Clamp		14050		
W	5/8" x 18" (or length req'd) Double Arming Bolt w/4 sq. nuts	8868			
X	guying detail - see detg No. ES-10 for specs.				
Y	Ret Line Clamp	5152000CP		KEARNEY	
Z	Squeeze on basket, size required				X

DATE: 12-27-71		TITLE	
DRAWN BY: E. WINTER		DESCRIPTION: MATERIALS	
DESIGN BY:		CONOCO	
CHECKED BY:		PRODUCTION DEPT.	
APPROVED BY:		JOB: HOBBBS DIVISION	
SCALE: NONE		DRAWING NO.: ES-1	
		SHEET 1 OF 3	

RECEIVED

JUN 14 1977

OIL CONSERVATION COMM.
LEBBS, H. M.