

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
MA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	FLX1015G			X
MB	General Purpose "U" bolt clamp	UC310AGP			
MC	Lightening arrester, 10 KV				
MD	Single phase oil switch, 14.4 KV			MOBAM-EDSON KINGZ BLACKBURN W 561E5	
ME	Split bolt connector, size req'd				
MF	Bonding spec. see dwg No. ES-11 & ES-1A, Note 3				
MG	35' class 4 creosoted pine pole				
MH	Aluminum deadend piniform for ACSR, size req'd				
MI	30' class 6 creosoted pine pole				
MJ	OVERHEAD GND, 64 ACSR - If Req'd - Ref. Dwg ES-11.				
MK	ES-1A - Note 3				
ML	Ground connector, motor				
MM	600 V. secondary lightning arrester single phase			BLACKBURN W 561E5	X
MN	Greenfield type HF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors				
MO	req'd size lb fitting & cover & gasket				
MP	transformer tank grounding terminal	GW3-75			

DATE:	12-27-71	TITLE:	DESCRIPTION MATERIAL
DRAWN BY:	E. WINTER	CONOCO HOBBS DIVISION DRAWING NO.: ES-1 SHEET 2 OF 3	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE:	NONE	JOB:	PROD. DEPT.
			REC. SPECS

RECEIVED

JUL 14 1977

OIL CONSERVATION COMM.
1998S, H. M.