

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MERS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	FZXX1015G			X
BB	General Purpose "H" bolt clamp	UC510AGP			
CC	Lightening arrester, 10 KV				
DD	Single phase oil switch, 14.4 KV			MORGAN-EDISON KVMC2 BLACK BURN W. STILES	
EE	split bolt connector, size req'd				
FF	Grounding specs. see dwg No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend Preforms for ACSR, size req'd				
JJ	30' class 6 creosoted pine pole				
KK	OVERHEAD GRND, #4 ACSR - If Req'd - Ref. Dwg ES-11, ES-1A - Note 3				
LL	Ground connector, motor			RELANDY AC-22	
MM	600 V. secondary lightening arrester single phase				X
NN	Greenfield Type FF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
OO	req'd size LB fitting & cover & gasket				
PP	transformer tank grounding terminal	GW5-15			

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WINTER		CONOCO HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	DRAWING NO: ES-1
		SHEET 2 OF 3	