

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	F2XR1015G			
BB	General Purpose "U" bolt clamp	UC510AGP			X
CC	Lightening arrester, 10 KV				
DD	Single phase oil switch, 14.4 KV			MYRAM-EDISON KMMC2	
EE	split bolt connector, size req'd			BLACK BURN "H" SITES	
FF	grounding spec. see dwg No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend preforms for ACSR, size req'd				
JJ	30' class 6 creosoted pine pole				
KK	OVERHEAD GRND, #4 ACSR - If Req'd - Ref. Dwg ES-11, ES-1A - Note 3				
LL	ground connector, motor				
MM	600 V. secondary lightening arrester single phase			PLANDY KC-22	X
NN	Greenfield Type EF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
OO	req'd size LB fitting & cover & gasket				
PP	transformer tank grounding terminal	GW5-15			

DATE: 12-27-71		TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WINTER		CONOCO PRODUCTION DEPT. HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	DRAWING NO: ES-1
		SHEET 2 OF 3	