

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM-17446
2. NAME OF OPERATOR The Superior Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME N.A.
3. ADDRESS OF OPERATOR P. O. Box 71, Conroe, Texas 77301		7. UNIT AGREEMENT NAME Government "L"
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL & 1980' FNL Sec. 18 - T24S - R34E		8. FARM OR LEASE NAME Government "L"
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	9. WELL NO. 1
		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18 - T24S - R34E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Weekly Report

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12-1/4" hole to 13,000'. Ran electric logs. Ran 10-3/4" casing to 13,000'. Cemented 10-3/4" casing w/250 sxs Class "H" w/2% Low Dense & 1% HR2, slurry wt. 12.5 ppg. followed w/250 sxs Class "H" w/1% CFR2, slurry wt. 15.7 ppg. Cut 10-3/4" casing & NU BOP's. Drilled out cement. Tested casing to 2500#. OK. Drilled out shoe @ 13,000'. Drilled 5' of new formation. Now preparing to test casing shoe.

18. I hereby certify that the foregoing is true and correct

SIGNED

Carl Ross

Carl Ross

TITLE

Jr. Petroleum Engineer

DATE Dec. 13, 1977

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DEC 19 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side