

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030174 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

W.H. Rhodes "B" Federal NCT

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Rhodes Yates

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 28, T-26-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ GAS ☐
WELL ☒ WELL ☐ OTHER

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P.O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FSL & 660' FEL of Section 28, T-26-S, R-37-E, Unit
Letter 'P', Lea County, New Mexico

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

2965' (GR)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Total Depth 3460'
8-5/8" OD 24# K-55 csg set @ 655'

1. Ran 3446' (86 jts) 5-1/2" OD 14# K-55 csg & set @ 3460'.
2. Cemented 5-1/2" csg w/700 sx TLW cement containing 8# salt per sack. Followed with 250 sx 50-50 Polmix Class 'H' cement containing 2% gel & 5# salt per sack. Job complete 5:30 a.m. 1-26-78. WOC in excess of 18 hrs.
3. Tested 5-1/2" OD csg w/1500# for 30 minutes, 12:00-12:30 p.m., 1-28-78. Tested OK. Job complete 12:30 p.m., 1-28-78.

Cement circulated

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Asst. Dist. Supt.

DATE

1-31-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

FEB 3 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side