

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
TEXACO Inc.

3. ADDRESS OF OPERATOR  
P. O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL & 1980'  
AT TOP PROD. INTERVAL: FEL (Unit Letter  
AT TOTAL DEPTH: 'J')

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
LC-030174(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
-

7. UNIT AGREEMENT NAME  
-

8. FARM OR LEASE NAME  
W.H. Rhodes 'B' Fed. NCT-2

9. WELL NO.  
5

10. FIELD OR WILDCAT NAME  
Rhodes Yates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 28, T-26-S, R-37-E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2966' (GR)

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

JUN 9 1981

U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

NOTE: Report results of multiple completion or zone change on Form 9-330.)

To: Open Add'l Yates & Treat

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rig up. Pull rods & pump. Install BOP. Pull tubing.
2. Set RBP @ 3270' & spot 10' Sand on plug.
3. Perforate 5 1/2" Csg w/1-JSPF @ 3124', 29', 31', 48', 51', 74', 76', 82', 84', 3201', 03', 07', 16', 24', 42', 47', & 3252'.
4. Set pkr. @ 3050'. Acidize perfs. 3124'- 3252' w/2000 Gals. Mud Acid & 28 Ball Sealers.
5. Frac w/20,000 Gals. CO<sub>2</sub> & 20,000 Gals. x-linked gelled water containing 38,000# 20/40 Sand & 37,000# 10/20 Sand. Clean out & pull RBP.
6. Set RBP @ 3100' & spot 10' Sand on plug.
7. Perforate 5 1/2" Csg w/1-JSPF @ 3007', 09', 16', 19', 34', 38', 43', 52', & 3061'.

(Continued on attached sheet)

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jack K. Hoff TITLE Asst. Dist. Mgr. DATE 6-4-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

APPROVED  
DATE 6-4-81  
JUN 11 1981  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR