UNITED STATES

## DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

5. LEASE	
NM - 25741	
6. IF INDIAN, ALLOTTEE OR TRIBE	NAME

15. ELEVATIONS (SHOW DF, KDB, AND WD)

SUNDRY NOTICES AND REPORTS ON WELLS to not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME Rhodes Yates Unit	
servoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
I. oil gas other	Rhodes Yates Unit	
well gas other	9. WELL NO.	
2. NAME OF OPERATOR	13	
EXACO Inc.	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Rhodes Yates	*

O. Box 728, Hobbs, New Mexico 88240 11. SEC., T., R., M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AREA 660' FSL & 660' FWL Sec. 27, T-26-S, R-37-E AT SURFACE: (Unit Letter 'M') 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: New Mexico AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

> 2975' (GR) SUBSEQUENT REPORT OF: (NOTE: Report results of multiple completion or zone change on Form 9–339) 191983

> > CL & GAS

14. API NO.

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* Addl. perfs. in Yates & Treat (other)

MINICIALS MAMT. SERVICE 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertment described and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rig up. Pull rods & pump. Install BOP. Pull tubing.

Set pkr. @ 3280'. Acidize perfs. 3312'-3349' W/2000 gals. 15% MSR Acid & 24 Ball Sealers. Pull pkr.

Perforate 5½" Csg W/1-JSPF @ 3167',77,81,86,89,97,3200',03,09,13,19,22,24,33,38,42,49 51,53,55,57,66,68,74,77,86,& 32921. Set RBP @ 3306' & pkr.@ 3100'. Acidize 5½" Csg perfs. 3167-3292, W/3000 gals.15% MSR

Acid & 54 Ball Sealers.

Frac  $5\frac{1}{2}$ " Csg perfs 3167'-3292' W/27,500 gals. X-Linked gelled 2% KCL Water & 27,500 Gals. of CO2 carrying 2000# 100 mesh sand, 53,000# 20/40 sand & 52,000# 10/20 sand in 2 stages using 490# rock salt between stages. Flush W/500 gal. gelled water & 500 gal CO2.

6. Pull pkr & RBP.

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

Install production equipment. Test & return to production.

Subsurface Safety Valve; Manu. and Type \_\_\_ \_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

TITLE Asst. Dist. Mgr. DATE APPROVED(This space for Federal or State office use) APPROVED B(CHESTER W. CHESTER CONDITIONS OF APPROVAL, IF ANY:

APR 2 0 1983