

(3)

- B. Drilling fluids will be allowed to evaporate in the drilling pit until pits are dry.
- C. Water produced during tests will be disposed of in the drilling pit. Oil produced during test will be stored in test tanks until sold.
- D. Current laws and regulations pertaining to human waste will be complied with.
- E. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24" of dirt. All waste material will be contained to prevent scattering by the wind. Location of trash pit is shown on Exhibit "C".
- F. All trash and debris will be buried or removed from the well site within 30 days, after drilling and/or completion operations are completed. Pits will be leveled as soon as possible.

8. Ancillary Facilities:

None Required

9. Well Site Layout:

- A. Exhibit "C" shows the relative location and dimensions of the well pad, mud pits, reserve pit, trash pit and location of major rig components.
- B. Only minor leveling will be required. No significant cuts and fills will be necessary.
- C. The reserve pit will be plastic lined.
- D. The pad and pit area has been staked and flagged.

10. Plans for Restoration of the Surface:

- A. After completion of drilling and completion operations, all equipment not needed for operations will be removed. Pits will be filled and location cleaned of all trash and junk.
- B. Any ungarded pits containing fluids will be fenced until they are filled.
- C. After abandonment of the well, surface restoration will be in accordance with an agreement with the surface owner.
- D. Drilling operations on this well will begin on November 1, 1977 and will last 90 days.

1-21-1977

CIL CONSULTING CORP.
HOBBS, N. M.