

5-USGS-HOBBS

1-FILE

1-ENGR

Form 9-331
(May 1963)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-21644

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ GAS ☐ OTHER ☐ INJECTION WELL

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

UNIT LETTER I, 760' FEL and 1980' FSL

7. UNIT AGREEMENT NAME

MYERS LANGLIE MATTIX UNIT

8. FARM OR LEASE NAME

MYERS LANGLIE MATTIX UNIT

9. WELL NO.

32

10. FIELD AND POOL, OR WILDCAT

LANGLIE MATTIX

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 25-23S-36E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3344' GR

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 11-23-77. Drilled 11" Hole to 500'. Set 8-5/8" 8Rd K-55 24# R-3 Casing @ 500'. Cemented with 150 Sxs. B.J. Lite with 6% Gel and 1/4# Celoflakes/Sk. and 150 Sxs. Class "C" with 2% CaCl₂ and 1/4# Celoflakes/Sk. Cement Circulated. Tested 8-5/8" casing with 1000# for 30 minutes. No drop in pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE AREA SUPERINTENDENT

DATE 12-28-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

DEC 30 1977

CC: Amoco-Levelland
Gulf-Midland
Texaco-Midland

/bh

J. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side