úE* (Other instruction | reverse side)

Form approved. Budget Bureau No. 42-R1425.

UNITED STATES

(May 1963)	UNIT	ED STATES	· ·	Other instr reverse		5 , -		
	DEPARTMENT)R		5. LEASE DESIGNA	TION AND SERIAL NO.	
GEOLOGICAL SURVEY						NM - 21644		
APPLICATION	N FOR PERMIT T	O DRILL, I	DEEPEN	. OR PLUG	BACK		OTTEE OR TRIBE NAME	
la. Type of Work					_			
DRI	LL 🖄	DEEPEN [PLUG BA		7. UNIT AGREEME		
b. TYPE OF WELL G.	AS 🗀	njection W	oll singi	E MULT	TPLE []	1yers Langi	ie Mattix Un	
WELL W	ELL OTHER I	njection w	C 1 1 ZONE	IAJ ZONZ		Mvers Langl	ie Mattix Un	
Getty Oil Company						9. WELL NO.		
3. ADDRESS OF OPERATOR		32	•					
	Hobbs, New Mexi					10. FIELD AND PO		
4. LOCATION OF WELL (R At surface	eport location clearly and	in accordance wit	h any Stat	e requirements.*)	-	Langlie Ma		
Unit Letter I	, 760' FEL and	1980' FSL,	Sec. 25	5-23S-36E		AND SURVEY (OR BLK. OR AREA	
At proposed prod. zon	e					25-23S-36E		
4. DISTANCE IN MILES	AND DIRECTION FROM NEAR	EST TOWN OR POS	r office*			12. COUNTY OR PA	RISH 13. STATE	
8 miles north	of Jal, New Me	xico				Lea	N.M.	
LOCATION TO NEAREST				l m		ACRES ASSIGNED IS WELL	40	
PROPERTY OR LEASE I (Also to nearest drig	g. unit line, if any)	660'		280			40	
13. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 1220				SED DEPTH	-	Rotary		
21. ELEVATIONS (Show who	LIASO, III					ū	E WORK WILL START*	
3344' Gr.	21, 101, 010,					11-1-7		
23.	P	ROPOSED CASIS	IG AND C	EMENTING PROG	RAM	,		
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER F	оот	SETTING DEPTH		QUANTITY OF C	EMENT	
11	8 5/8	24		500	200	sacks		
7 7/8	5 1/2	15.	5	3700		sacks		
					WHI	LE DRILLING AN	b (ESTING."	
Ť1	 	u. da:33.ad	- F	ha austraa	+ + - + -	al danth af	2 7001 with	
	osed well will The pump and p							
casing and ce	ment will be ci	rculated to	n the a	urface on t	he 8 5/8'	" and 5 1/2	" casing.	
The 5 1/2" ca	sing will be pe	rforated a	s indic	cated by ele	ctric lo	qs opposite	the the	
Langlie-Matti	x formation.							
The dril	ling fluid will	be brine	water a	ind mud of s	ufficient	t weight to) condition	
	ging and running	casing to	3700'.	Blow out p	reventors	s will be i	nstalled and	
tested to 500	10 ps1.					- :		
Note: A DV To	ool will be set	at 2800' i	n the S	5 1/2" casin	a	色四层双层		
Unless Dri		1000 II	0116	1,2 003///				
Google 16d.		igen ja varia en				1977		
	2-14-7	8			· .	, rer i		
Expires						THE THE AL SU		
N ABOVE SPACE DESCRIBE one. If proposal is to preventer program, if an	: PROPOSED PROGRAM: If p drill or deepen directiona v	oroposal is t≏ deep lly, give pertinent	en or plug t data on s	back, give data on ubsurface locations	present produ	ctive zone and nu- knd true vertical	aposed new productive depths. Give blowout	
4.	1-7							
SIGNED	IVI (Land		LE Area	a Superinten	dent	DATE 10	0-17-77	
	ral or State office use)				15			
(Z Dj.mac vot z cae		A COLED TO	JK	Av State	1	冠口人	g .EL	
PERMIT NO.	CONDITION	S OF APPI	₹O VAĽ	PROVAL DATE	Sold of many of the first	- AM		
APPROVED BY		TIT	T.E	1.3.2.	N 1 6 131	1 CHATE	<u> </u>	
	A C. TITLAND !			1 1 2 00	-	1		