

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. E. LaMunyon

9. WELL NO.

45

10. FIELD AND POOL, OR WILDCAT

North Teague Devonian

11. SEC., T., R., M., OR BLE. AND
SURVEY OR AREA

Sec 27, T-23S, R-37E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

GULF OIL CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

500' FNL & 990' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3286' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Fill Cellar

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 7-7/8" hole (7600') @ 6:50 P.M., 7-25-78. Ran 5-1/2" casing as follows: 28 jts (1131.04') 17# N-80 LT&C; 53 jts (1650.86') 15.50# K-55 LT&C; 73 jts (1936.81') 15.50# K-55 ST&C; 78 jts (2465.19') 17# K-55 LT&C; 12 jts & 1 cut jt (400.10') 17# N-80 LT&C casing for a total of 244 jts & 1 cut jt (7584'). Set @ 7600'. Cement with 1415 sacks of Gulfmix with 1/4# Flocele, 225 sacks of Class "C" with 6% gel + .5% CFR-2 & 550 sacks of Class "C" with .5% CFR-2. Plug down @ 10:45 A.M., 7-28-78. Cement circulated. Wait on cement over 72 hours.

Tested 5-1/2" casing to 2800# for 30 minutes; held o.k.

Piped valves above ground level off casing string. Filled cellar. Cleaned location. Set anchors.

RECEIVED

AUG 1 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Glyn Stone

TITLE Acting Area Engineer

DATE 08-02-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

A. A. L.
AUG 3 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side