

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.
17191

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

GIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Coquina Oil Corporation	8. Farm or Lease Name Alexander
Address of Operator P. O. Drawer 2960, Midland, Texas 79702	9. Well No. 1
Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>10</u> TOWNSHIP <u>24S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3583' KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

RE-DRILL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out CIBP @ 12,010'. Set CIBP @ 12,820' and capped with 50' of cement on top of plug. Perforated Atoka zone with 1 jspf from 12,623-686' (44 holes). Acidized with 2500 gallons of 15% HCL acid. Ran in hole with tubing and packer. Swabbed well dry with no additional fluid or gas entry. Set CIBP @ 12,600', capped with 40' of cement to abandon Atoka zone. Perforated Wolfcamp Sand with 1 jspf from 11,916-12,153' (17 holes). Acidized with 2000 gallons MS-15% HCL and fraced with 15,000 gallons YF-4 with 2000# 100 mesh sand and 17750# 20-40 sand with 1500 gallons of 15% HCL ahead of frac. Swabbed and recovered 18 barrels over load with no oil or gas recovery.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Steve Gurley TITLE Production Engineer DATE June 23, 1981

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: