

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ convert to wiw

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
7990 IH 10 West, San Antonio, TX 78230

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FNL & 660 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☒
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) ☒ convert to WIW

5. LEASE

NM-7951

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Leonard Bros.

9. WELL NO.

26

10. FIELD OR WILDCAT NAME

S. Leonard

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13, T26S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DE KDB, AND WD)
3010 KB, 2998 GREA OF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. MIRU PU.
2. Pull rods and pump
3. NUBOP. Tag bottom and pull tubing. If there is fill above 3524', clean out sand.
4. RIH w/ 2 3/8" tubing and treating PKR, set PKR at + 3400'. Treat perms w/xylene/15% HCL. Flush tbg w/2% KCL.
5. Unset PKR. POOH w/PKR and tbg.
6. RIH w/plastic coated TBG and plastic coated Guiberson uni-packer I. Circulate hole w/2% KCL containing corrosion inhibitor, oxygen scavenger and biocide (85 bbls should circulate hole).
7. Set PKR at + 334'. NDBOP.
8. Hook up injection line.
9. RDPU.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert M. Mathew TITLE Prod. Eng. Supv. DATE 3-22-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED

APR 24
R. B. Pritchard
ACTING DISTRICT ENGINEER

RECEIVED

APR 26 1984

O.C.O.
MOBBS OFFICE