

NEW MEXICO OIL CONSERVATION COMMISSION

N.O. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1484

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Doyle Hartman	8. Farm or Lease Name Citgo "AS" State
3. Address of Operator 508 C & K Petroleum Building, Midland, Texas 79701	9. Well No. 3
4. Location of Well UNIT LETTER <u>C</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>24-S</u> RANGE <u>36-E</u> NMPM.	10. Field and Pool, or Wildcat Langlie Mattix
15. Elevation (Show whether DF, RT, GR, etc.) 3368 G. L.	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled well to a total depth of 3801 RKB. Ran 119 jts (3804 feet) of 5 1/2 OD, 14 lb/ft, J-55, ST&C casing and landed at 3801 RKB. Cemented casing with 450 sx of API Class-C cement containing 3% Halliburton Econolite and 1/4 lb/sx Flocel followed by 350 sx of a 50-50 blend of API Class-C cement and Pozmix "A" containing 18% salt and 1/4 lb/sx Flocel. Plug down at 3:00 PM CDT 8-9-78. Circulated 219 sx of excess cement to pit. Pressure tested casing to 1500 psi. Pressure held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Doyle Hartman TITLE Operator-Part Owner DATE 8-10-78

APPROVED BY John Runyan TITLE Geologist DATE AUG 14 1978  
CONDITIONS OF APPROVAL, IF ANY

RECEIVED

AUG 11 1978

OIL CONSERVATION COMM.  
MOBILE, AL