

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

GULF OIL CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1780' FSL & 1880' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3284' GL

9. WELL NO.

46

10. FIELD AND POOL, OR WILDCAT

North Teague Devonian

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 22, T-23S, R-37E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running & Cementing Surface

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☒

Casing

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M-G-F Drilling Company Rig #10 spudded a 12-1/4" hole @ 9:30 P.M., 10-19-78. Reached TD (1100') of 12-1/4" hole @ 12:45 P.M., 10-20-78. Ran 27 joints (1082') of 8-5/8" 24# K-55 ST&C 8 RT casing. Set @ 1095'. Cemented with 300 sacks of Class "C" with 6% gel & 200 sacks of Class "C" with 2% CaCl₂. Plug down @ 5:30 P.M., 10-20-78. Cement circulated. Wait on cement for 18 hours.

Tested 8-5/8" 24# casing to 1500# for 30 minutes; held o.k.

Began drilling 7-7/8" hole @ 1:30 P.M., 10-21-78.

18. I hereby certify that the foregoing is true and correct

SIGNED

N. B. Sikes, Jr.

TITLE

Area Engineer

DATE

10-23-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 24 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side