



Getty Oil Company

Central Exploration and Production Division

P. O. Box 730

Hobbs, New Mexico 88240

February 13, 1979

New Mexico Oil Conservation Commission

P. O. Box 1980

Hobbs, New Mexico 88240

CINTA ROJA "10" WELL NO. 1

DEVIATIONS

Unit Ltr. F, 1980' FNL & 1650' FWL, Sec. 10, T-24S,R-35E

<u>DEPTH</u>	<u>DEGREES OFF</u>	<u>DEPTH</u>	<u>DEGREES OFF</u>
200	1/4	7630	1
420	1/2	8130	1 - 1/4
422	1/2	8454	3/4
850	1/2	8947	3/4
1050	1	9440	1
1271	1	9850	1
1460	1 - 1/4	10389	1
1640	1/2	10900	2
1901	3/4	11231	1 - 1/2
2184	3/4	11455	1 - 1/4
2467	3/4	11745	1 - 1/4
2752	1/4	12170	2
3129	3/4	12268	1 - 3/4
3600	2 - 1/2	12564	1 - 1/2
3700	1 - 3/4	12839	1/2
3800	2 - 1/4	13114	1/2
4000	2	13345	1 - 1/4
4400	2 - 1/4	13535	2
4900	2 - 1/4	13617	2
5400	2	13812	2 - 3/4
5620	2 - 1/4	14049	3
6129	1 - 1/2	14271	3 - 1/4
6634	1 - 1/4	14464	4
7139	1	14600	4 - 1/2

The above information is correct and complete to the best of my knowledge.

RECEIVED
OCT 01
O.C.D. HOBBS, OFFICE

[Signature]
Dale R. Crockett, AREA SUPERINTENDENT

Page 2
Cinta Roja 10 #1
C-105

No. 26 - Dresser Atlas ran: Neutron-Density surface-TD, Acoustilog 5394'-TD, Dual Laterolog-Micro Laterolog 5394'-TD, and Density-Neutron, BHC Acoustilog, and Dual Laterolog-Micro Laterolog 12,150-14,598'.

Schlumberger ran Gamma Ray and Spectroscopy Log (TD) 14,481-13,900' and Cement Bond Log 14,476-11,888'.

Cardinal ran Production Log, Fluid Density, Temperature Log, and Radioactive Tracer.

No. 32 - 3000 gals. 7 1/2% MS acid, 33 ball sealers, 122,000 N₂, 22,500 gals. MS sand frac, 9,000# 20-40 sand, 43 tons CO₂, 8,000 gals. 3% acid, 14,000 gals. X-Link gel, 4000# 100 sand, 4900# bauxite, 5860# 20-40 sand, and 20 tons CO₂.

FORMATION TOPS

Permian

Rustler	1190
Tansil (Capitan)	3728
Cherry Canyon	6542
Brushy Canyon	7743
Bone Springs	9048
1st Bone Springs Sd	9920
Wolfcamp	11767

Penn.

Strawn	12,622
Atoka	13,120
Morrow Lime	13,564
Morrow Clastics	13,750
Morrow "D" Marker	14,070
Total Depth	14,600