

Form 7-631  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM 23199

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilson 21 Federal

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT Und.  
Comanche Stateline Yates11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 21, T26S, R36E

12. COUNTY OR PARISH 13. STATE

Lea

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☒ GAS ☐  
WELL WELL OTHER

2. NAME OF OPERATOR

HNG Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 2267, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

990' FWL &amp; 1700' FNL of Sec. 21

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

2934' GR

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☒CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)16. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*Set CIBP at bottom of 8-5/8" casing set at 1352' w/35 feet cement on top  
using 25 sx C1 H cement.

Fill casing w/10# brine.

Set a plug from surface to 10 feet w/10 sx C1 H cement, and install  
dry-hole marker.

RECEIVED

JAN 16 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty A. Gildon

TITLE

Regulatory Clerk

DATE

January 15, 1980

APPROVED

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side