

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O.C.G.

Form approved
Budget Bureau No. 42 R1424
OFFICE DESIGNATION AND SERIAL NO.

N.M. 8447

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different level.
Use "APPLICATION FOR PERMIT" for such proposals.

INDIAN, ALLOTTEE OR TRIBE NAME

#1

UNIT AGREEMENT NAME

Woolworth Ranch Unit

FAVOR OR LEASE NAME

WELL NO.

1

FIELD AND POOL, OR WILDCAT

Cinta Rojo Morrow

SEC. T., R., M., OR B.M. AND
SURVEY OR AREA

Sec. 4, T-24S, R-35E

12. COUNTY OR PARISH 13. STATE

New Mexico

TO ELEVATIONS (Show whether in feet or meters)

3386.7' G.R.

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NATURE OF INTENTION TO:

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

WELL OR ALTER CASING

WATER TREATMENT

RE-ENTER COMPLETE

WATER RE-ENTER

ABANDON*

WATER SHUT-OFF

CHANGING PLANS

WATER SHUT-OFF

FRAC TREATMENT

SHOOTING OR ACHILLING

OTHER

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Not a Report results of multiple completion on Well
Completion or Recommendation Report and Log form.)

NOTE: This form is to be used for all wells, whether drilled or not, and for all types of work, including estimated date of starting any work on this work.

- 5/1/79 Move in and rig up pulling unit, install B.O.P.
5/1/79 Run Tubing to 10,700', Circul. mud out, top of liner at 11,922', drill 60' cement, Plug back TD at 14,294'.
5/1/79 Test tubing in hole 8500 lbs., 455 jts., no leaks, spotted 500 gallons MSA Acid at 14,290', packer 14,011', set 4 1/2 Baker lock set, packer at 14,011'.
5/1/79 Rig up Schlumberger to perforate, Perforate as follows: 14272-14275 3' 6 holes, 14259-14267 8' 16 holes, 14073-14078 5' 10 holes, 14054-14059 5' 10 holes
swabbed down to 13,000', small flare of gas.
5/16/79 Tubing pressure 300 lbs., fluid level 12,000', blowed down in 30 minutes, no fluid, well swabbed dry, gas gradually increased, closed in for night.
5/17/79 Tubing pressure 1350, blowed down in 40 minutes, flowed well 2 1/2 hrs. with some mist to pit, closed in for night.
5/18/79 Tubing pressure 1250, run swab 12,000' to fluid, rig up Halliburton, treat with 6000 gallons of Morrow Flow BC, 2 gallons of FR24 per 1000 gallons, average rate 6.5 bbls. per minute, 2% KCL water plus nitrogen, flowed back 2 1/2 hrs., gas surfaced, swabbed down to 13,000', gas increased slightly, closed in for night.

SEE ATTACHMENT A

I hereby certify that the foregoing is true and correct

SIGNED

Arnold Hawkit

TITLE

Suplt

(Leave space for Federal or State office use)

REMOVED BY

REVISIONS OF APPROVAL IF ANY:

TITLE

DATE

10-18-79

ACCEPTED FOR RECORD

OCT 22 1979

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse