

hauled to an approved disposal system, or a separate disposal application will be submitted to the USGS for approval.

E. Oil produced during operations will be stored in tanks until sold.

F. Current laws and regulations pertaining to the disposal of human waste will be complied with.

G. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste materials will be contained to prevent scattering by the wind.

H. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.

#### 8. ANCILLARY FACILITIES.

A. None required.

#### 9. WELLSITE LAYOUT.

A. Exhibit C shows the relative location and dimensions of the well pad and reserve pits. The new access road will enter the pad at the southeast corner of the pad.

B. The ground surface at the wellsite is relatively level, with a gentle rise to the north. Only minor cut and fill will be required in constructing the well pad.

C. The reserve pits will be plastic-lined.

D. The pad and pit area has been staked and flagged.

#### 10. PLANS FOR RESTORATION OF THE SURFACE.

A. After drilling and/or completion operations have been finished, all equipment and other material not needed for further operations will be removed. Pits will be filled and the location cleaned of all trash and junk, so as to leave the wellsite in as aesthetically pleasing a condition as possible.

B. Any unguarded pits containing fluids will be fenced until they have been filled.

C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the BLM and the USGS will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment.

#### 11. OTHER INFORMATION.

A. The proposed wellsite is located in a relatively level area, with minor surface undulations. This also applies to the route of the proposed new access road.

