

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well <input checked="" type="checkbox"/> gas well <input type="checkbox"/> other <input type="checkbox"/>
2. NAME OF OPERATOR Amoco Production Company
3. ADDRESS OF OPERATOR P. O. Drawer "A" Levelland, TX 79336
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 890' FAL & 890' FWL, Sec. 18 (Unit D, NW 1/4, NW 1/4)
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spud; casing, casing test <input checked="" type="checkbox"/>	

5. LEASE LC-030180-X (a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Farnsworth Federal "A"
9. WELL NO. 12
10. FIELD OR WILDCAT NAME Scarborough-Yates-Seven Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 18-26-37
12. COUNTY OR PARISH Lea
13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 2957 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 1-1-79, Verna (Rig #14) spudded a 12 1/4" hole at 3:30 pm. Drilled to TD 1133' and ran 9-5/8" 32.3# H-40 ST&C casing set at 1133'. Cemented with 200sx Thickset, 400sx Howcolite, and 100sx Incor plus 2% CACL. Circulated 250 sx. P.D. 1:45 PM 1-4-79. WOC 18 hours. Test casing 1000# for 30 min. Test ok. Reduce hole to 8-3/4" and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Cox TITLE Admn. Supervisor DATE 1-8-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

- 0+4 - USGS-H
- 1 - Houston
- 1 - SUSP
- 1 - DE

*See Instructions on Reverse Side

RECEIVED
JAN 10 1979
U.S. GEOLOGICAL SURVEY
HOBBES, NEW MEXICO

RECEIVED
JAN 10 1964
U.S. AIR FORCE
HEADQUARTERS
AIR FORCE
WASHINGTON, D.C.

1944 10 29

100-443887-100