

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO U. S. G.
SUBMIT IN TRIPLICATE
(Other instructions on
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM-20975
2. NAME OF OPERATOR Union Oil Company of California		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 671 - Midland, Texas 79702		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL and 1980' FEL		8. FARM OR LEASE NAME Paduca Federal
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3525.5' GR.	9. WELL NO. 1
		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T-24-S, R-32-E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) <u>Set production liner</u>	☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- 4-11-79 - W.O.C. 24 hours. Ran temperature survey, indicated top of cement outside 7-5/8" OD casing at 4,400' from surface. Installed 10,000 psi B.O.P.'s
- 4-13-79 - Tested casing and blind rams to 7000 psi and choke manifold to 9000 psi, held OK. Ran 6-1/2" bit, drilled from 12,834' to 15,531', total depth. Reached total depth at 4:15 A.M. 6-9-79.
- 6-9-79 - Schlumberger ran electrical logs.
- 6-11-79 - Ran 73 jts. (2,921') of 5-1/2" OD 20# P-110 AB FL-45 new liner set at 15,531', tie-back sleeve at 12,622'. Cemented with 335 sk Class "H" cement. Job completed at 10:00 A.M. 6-11-79. W.O.C.
- 6-12-79 - Drilled out cement to top of 5-1/2" OD Liner at 12,622', tested liner to 2500 psi, held 1 hour OK.

RECEIVED

SEP 19 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED J.R. Hughes J.R. Hughes


TITLE District Drilling Supt. DATE Sept. 17, 1979

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED

SEP 25 1971

O.C.D. HOBBS, OFFICE