

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructor
verse side)Form 9-331
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18644

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilson 8 Federal

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Sioux Tansill Yates SR

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8, T26S, R36E

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

HNG OIL COMPANY

3. ADDRESS OF OPERATOR

Box 2267, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2140' FSL & 1787' FEL, Section 8.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2971' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF: 5-27-82

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-24-82 - Set Pengo Cement retainer at 3104'; pump 12 bbls 10 ppg brine into formation; circ hole w/85 bbls 10 ppg brine salt mud; sting into retainer and squeeze perfs 3201 - 3562 w/90 sx. C1 H cement leaving 25 feet of cement on top of retainer.

6-25-82 - Cut and recovered 2020 feet of 14# 5-12/" Casing.
mix and spot 50 sx. C1 H cement 2070 - 1920'.
Circ. hole with 110 bbls 10 ppg brine; mix and spot 70 sx. C1 H from 1462' - 1362'.

6-26-82 - Tagged top of cement plug at 1368'.
mix and spot 25 sx. C1 H cement from 90 to surface.
Cut off head, weld on plate & dry-hole marker; cut off anchors, and
clean up location.

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty Gildon
Betty Gildon

TITLE Regulatory Analyst

DATE June 28, 1982

(This space for Federal or State Approval)

APPROVED

APPROVED (Sig. Sgd.) PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

FEB 9 1983

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

RECEIVED
JUN 30 1982OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO