

DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)  
SOUTH CENTRAL REGION  
GEOLOGICAL SURVEY

SUBJECT NUMBER NO. 42-R1424  
LEASE DESIGNATION AND SERIAL NO.

COPY 18644

# SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR HNG OIL COMPANY		8. FARM OR LEASE NAME Wilson 8 Federal	
3. ADDRESS OF OPERATOR Box 2267, Midland, Texas 79702		9. WELL NO. 5	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  2140' FSL & 1787' FEL, Section 8.		10. FIELD AND POOL, OR WILDCAT Sioux Tansill Yates SR	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2971' GR	
		12. COUNTY OR PARISH Lea	
		13. STATE NM	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

### SUBSEQUENT REPORT OF:

5-27-82

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recapture Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-24-82 - Set Pengo Cement retainer at 3104'; pump 12 bbls 10 ppg brine into formation; circ hole w/85 bbls 10 ppg brine salt mud; sting into retainer and squeeze perfs 3201 - 3562 w/90 sx. C1 H cement leaving 25 feet of cement on top of retainer.

6-25-82 - Cut and recovered 2020 feet of 14# 5-12/" Casing.  
mix and spot 50 sx. C1 H cement 2070 - 1920'.  
Circ. hole with 110 bbls 10 ppg brine; mix and spot 70 sx. C1 H from 1462' - 1362'.

6-26-82 - Tagged top of cement plug at 1368'.  
mix and spot 25 sx. C1 H cement from 90 to surface.  
Cut off head, weld on plate & dry-hole marker; cut off anchors, and clean up location.

## 18. I hereby certify that the foregoing is true and correct

SIGNED

*Betty Gildon*  
Betty Gildon

TITLE Regulatory Analyst

DATE

June 28, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED  
JUN 30 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY

71