

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
BOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18644

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilson 8 Federal

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Sioux Tansill Yates SR

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 8, T26S, R36E

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
HNG OIL COMPANY

3. ADDRESS OF OPERATOR
Box 2267, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FEL, Sec. 8.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2979' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF: 5-27-82

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-22-82 - Set Pengo cmt retainer at 3173'; pump 12 bbls 10 ppg brine into formation; circ. hole w/87 bbls gel mud, sting into ret; squeeze perforations 3275' - 3554' w/90 sx. C1 H cement; 16 ppg; leaving 25' cement on top of retainer.

6-23-82 - Cut and recovered 1934 feet of 5-1/2" 14# casing.
Mix and spot 50 sx. C1 H 1984' - 1884'
Mix and spot 70 sx. C1 H 1473' - 1373' - Tagged top at 1352'.

6-24-82 - Mix and spot 25 sx. C1 H 90' to surface.

6-25-82 - Cut off head; weld on plate and dry-hole marker, cut off anchors, and cleaned up location.

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty E. Gilson

TITLE Regulatory Analyst

DATE June 28, 1982

(This space for Federal or State use)

APPROVED BY: (Orig. Sgd.) PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

FEB 9 1983

FOR

JAMES A. GILLHAM *See Instructions on Reverse Side
DISTRICT SUPERVISOR

RECEIVED
JUN 30 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO