

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY TO U. S. G.
SUBMIT IN TRIPLICATE*
(Other instructions re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18644

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilson 9 Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Sioux Yates

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9, T26S, R36E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2958' GR

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SIDETRACK

SUBSEQUENT REPORT OF: 2-7-80

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Sidetrack

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

At a depth of 2900' a Gamma Ray Sonic logging tool, 36 feet in length, was lost in the hole. ~~On 3-5-80~~ A cement plug **WILL BE** set at 2900 feet w/300 sx ClH, 1% CFR-2, 10#/sx sd., 1.3#/sx salt, mix at 18.0 ppg. Top of the plug ~~is~~ at 2522 feet. ~~On 2-5-80~~
The hole was sidetracked at 2731 feet.

WILL BE

RECEIVED

MAY 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty W. Gildon
Betty W. Gildon

TITLE Regulatory Clerk

DATE 3-6-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side