

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER REFS. NO.	NO. SUB.
A	3 1/2" class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	high density wet Process porcelain pin insulator		463		
D	3/8" x 3" forged steel pin w/eq. washer, nut, & locknut	881			
E	5/8" x 12" machine hole w/ nut (or length req'd)	881/2			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole eq. washer	681/2			
G	5/8" HF locknut	351/2			
H	1/4" x 1 1/4" x 28" flat crossarm brace	712/8			
I	1/2" x 4" E2 Fetter Drive Log Screw	508754			
J	3/8" x 4 1/2" carriage bolt w/ Nut	86341/2			
K	3/8" HF locknut	3510			
L	Preformed Aluminum Alloy Armo Rod, size req'd				
M	tie wire 66 strong alum. alloy				
N	foxy insulator (extension link)				
O	3 1/2" class 5 creosoted pine pole				
P	Aluminum double end Squeeze on Connector for ACSR, Aluminum, or Copper-size req'd				
R	6" Suspension Insulator	66200			
S	5/8" Standard Oval Eye Nut	6502			
T	Primary Dead End Clamp		14050		
U	5/8" x 18" (or length req'd) Double Arming Bolt w/eq. nut	8868			
V	Boying detail - see det. No. ES-10 for spec.				
X	Hot Line Clamp				
Y	Squeeze on basket, size required	51820A/C/P			
Z					

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB:	HOBBBS DIVISION
		DRAWING NO: ES-1	
		SHEET 1 OF 3	