

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC - HOBBS
1-R. J. Starrak- Tulsa
1-A. B. Cary-Midland
1-ELB-Engr

1-HC-Foreman
1-File ✓
1-Gulf
1-HNG
1-Mesa

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
6. Farm or Lease Name	
HNG State 4-F	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSED TO DRILL OR TO REOPEN OR REEQUIP A WELL TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR REOPEN FOR SUCH PURPOSES.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

1. Name of Operator
Getty Oil Company

2. Address of Operator
P. O. Box 730, Hobbs, New Mexico 88240

3. Location of Well

UNIT LETTER F 1980 FEET FROM THE North LINE AND 1650 FEET FROM
THE West LINE, SECTION 4 TOWNSHIP 24-S RANGE 33-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3588'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☒
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

- 3-1-79 Schlumberger ran CNL-FDC, TD-5200' and DLL-RXO, TD-5200'.
- 3-3-79 Ran 321 Jts. 12,686' 7" OD 26# & 23# S-95, ST&C & LT&C Casing & Set @12,710'. Float Collar @12,660'. DV @8001'. 2 baskets below DV @8043' & 8082', Centralizers @12,695; 609; & 519.
- 3-4-79 Halliburton Cemented First Stage: w/250 sxs. Lite Wate, w/.6% Halad 9, 3# Gilsonite, 1/4# Flocele/sk. and 400 sxs. Class "H" Cement w/.3% HR-4/sk. 40 sxs. Cement Circulated.
Second Stage: 1000 sxs. Lite Wate w/.6% Halad 9, 3# Gilsonite, 1/4# Flocele/sk., and 200 sxs. Class "C" Neat Cement. Lost Circulation. Worth Well ran Temperature Survey & found top of cement @5145'. Waiting on Cement.
- 3-5-79 Waited on Cement 18 hrs. Pressured to 1000# for 30 minutes. o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 9/17/79

ORIG. SIGNED BY Jerry Sexton TITLE Dist 1, Supr.

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

SEP 20 1979