STATE OF NEW MEXICO								265
ST. TE OF INEVA MICKIGO	) .					90	- 7 ^	
TRGY AND MINERALS DEPART	TMENT OIL	CONSERVAT	ION DIVIS	ION		30- Form C-101	025-	# 10
HO, OF COPICO ACCEIVED		P, O, BOX				Revised 10		
DISTRIBUTION	s	ANTA FE, NEW I	MEXICO 875	) !		5A. Indicate	e Type of L	,005 <b>0</b>
SANTA FE FILE						STATE		rcc 🖸
U.S.G.S.						.5, State Oil	& Gas Lou	so No.
LAND OFFICE								
OPERATOR								1111
	FOR PERMIT T	O DRILL, DEEPEN	I, OR PLUG BA	/CK				
Type of Work						7. Unit Agre	ement Nam	0
DRILL X		DEEPEN		PLUG 8	ACK			
Type of Well						8. Farm or 1.	.ease Name	
FLL X GAS WELL Dame of Operator	R3HTO		ZONE X	MUL	ZONE	Steeler	· A	
James L. Evans						9. Well No.		
dress of Operator			*			3	15.1	
7.0						10. Field and Pool, or Wildcat		
cotton of Wall		A 4 4				Lang	ilie Ma	ttix
UNIT LETTER	L	OCATED UOU	FEET FROM THE	south	LINE			/////
1980 FEET TROM TH	west .	INE OF SEC. 20	TWIP. 23 S	se. 37	<b>Е</b> мыры			
				TTT	177777	12, County		1,444
						Lea		
				1111	11111	TTTT	11111	4,4,4
			19. Proposed Dep	th [1:	A. Formutio	u	20, Rolary	or C.T.
			3700		Queen		Rot	arv
levations (Show whether DF, K)	, , , , , , , , , , , , , , , , , , , ,	id & Status Plug. Bond	21B. Drilling Con			22. Approx	. Date Work	
	PIS	nket	Unknow	n		Nov	. 1/198	30
		PROPOSED CASING AN	ND CEMENT PROG	RAM				
SIZE OF HOLE IS	SIZE OF CASING	WEIGHT PER EOO	T SETTING D	EDTU	CACKEOL	CEMENT		T (C)
	SIZE OF CASING			EPTH	SACKS OF	CEMENT		TOP
13 3/8	8/58	32 #	3001	EPTH	SACKS OF	CEMENT	Circu	late
13 3/8 7 7/8	8/58 5 1/2	32 # 14 #	300° 3700				Circu Circ	late late
13 3/8	8/58 5 1/2  ailibility of rox. 300'. Doing to the control of the c	32 # 14 # igs drilling con ouble ram hydr be installed ar ement. Blow or at and complete	300° 3700  atractor is a raulicly opend drilling at preventer with approximation of the state of	inknov rated will pi rs will ox. 360	vn at the	is time. It preven	Circu Circu 8 5/8 conters, no. 3700	late late asing ninim ', wil
Due to lack of avawill be set at app. 400% # working prothen run 5 1/2 and and will log and powill remain on weather.	8/58 5 1/2  ailibility of r rox. 300'. D ressure, will d circulate c perforate, tre ell untill all c	igs drilling concuble ram hydral be installed and ement. Blow on at and complete completion wor	300' 3700  atractor is a raulicly opend drilling with approximate with a proximate with a p	inknovrated will pies will ox. 360 d.	vn at the bliow out occide then be compared to the period of the period	is time.  It preven o approx e moved 8 tubing.  VALID FOR XPIRES	Circu Circu 8 5/8 conters, noters, not	asing ninim ', wil string enter
Due to lack of avawill be set at app. 400% # working prothen run 5 1/2 and and will log and powill remain on weather.	8/58 5 1/2  ailibility of r rox. 300'. D ressure, will d circulate c perforate, tre ell untill all c	igs drilling concuble ram hydral be installed and ement. Blow on at and complete completion wor	300' 3700  atractor is a raulicly opend drilling with approximate with a proximate with a p	inknovrated will pies will ox. 360 d.	vn at the bliow out occide then be compared to the period of the period	is time.  It preven o approx e moved 8 tubing.  VALID FOR XPIRES	Circu Circu 8 5/8 conters, noters, not	asing ninim ', wil string enter
13 3/8 7 7/8  Due to lack of availl be set at app. 400# # working price then run 5 1/2 and and will log and p	8/58 5 1/2  ailibility of r rox. 300'. D ressure, will d circulate c perforate, tre ell untill all c	igs drilling concuble ram hydral be installed and ement. Blow on at and complete completion wor	300' 3700  atractor is a raulicly opend drilling with approximate with approximate with approximate with approximate with approximate with approximate and bell approximately ap	inknovrated will pies will ox. 360 d.	PROVAL PERMIT E UNLESS	is time.  It preven o approx e moved 8 tubing.  VALID FOR XPIRES	Circu Circu 8 5/8 conters, no. 3700 to oil a Preve	asing ninim ', wil string enter
Due to lack of avawill be set at app. 4000 # working prothen run 5 1/2 and and will log and powill remain on we will remain on which we will remain on we will remain on we will remain on which we will remain on the weak which will remain on the weak which we will remain on the will remain on the will remain on the weak which we	8/58 5 1/2  ailibility of r rox. 300'. D ressure, will d circulate c perforate, tre ell untill all c  osed program: ir rescam. If any.  above is true and con	igs drilling corouble ram hydra be installed and ement. Blow or at and complete completion wor	300' 3700  atractor is a raulicly opend drilling with approximate with approximate with approximate with approximate with approximate with approximate and bell approximately ap	inknovrated will pies will ox. 360 d.	PROVAL PERMIT E UNLESS	is time. It prevent o approxe moved B tubing.  VALID FOR XPIRES DRILLING	Circu Circu 8 5/8 conters, no. 3700 to oil a Preve	asing ninim ', wil string enter
Due to lack of avawill be set at app. 4000 # working prothen run 5 1/2 and and will log and powill remain on weather.	8/58 51/2  ailibility of r rox. 300'. D ressure, will d circulate c perforate, tre ell untill all c  after lyper cosed program: If procedure is true and con the viet	igs drilling corouble ram hydra be installed and ement. Blow or at and complete completion wor	300' 3700  atractor is a raulicly opend drilling with approximate with approximate with approximate with approximate with approximate with approximate and bell approximately ap	inknovrated will pies will ox. 360 d.	PROVAL PERMIT E UNLESS	is time. It prevent o approxe moved B tubing.  VALID FOR XPIRES DRILLING	Circu Circu 8 5/8 conters, no. 3700 to oil a Preve	asing ninim ', wil string enter

ONDITIONS OF APPROVAL, IF ANY