

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG - 3340	
7. Unit Agreement Name	
GMW - Pawnee Deep	
8. Farm or Lease Name	
White Eagle	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Gifford, Mitchell & Wisenbaker
3. Address of Operator
1280 Midland National Bank Tower
4. Location of Well
UNIT LETTER F, 1650 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 26-S RANGE 36-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
2909.80 GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran and set 20" 94# casing at 925'. Cemented with 1100 sacks of Haliburton Lite Weight cement with 2% Ca Cl, 12.4 pounds per gallon, and 600 sacks of Class "C" neat cement with 2% Ca Cl, 14.8 pounds per gallon. Had full circulation throughout job. Circulated out 5 sacks of cement. WOC 8 hours. Weld on companion flange and connect blowout preventers, 11 hours. Test pipe and blowout preventers to 500 psi for 30 minutes, held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. B. Stiff TITLE Production Engineer DATE 11/29/79

Orig. Signed by

Jerry Sexton

APPROVED BY Dietl, Supv.

TITLE _____

DATE DEC 3 1979

CONDITIONS OF APPROVAL, IF ANY: