

WELL NAME Lynn A No. 6 FIELD NMFU DATE 8-1-79
 AFE NO. ELEV. GRD KB PROPOSED TO 3720'
 LOCATION (SURF.) 1980' FNL & 2310' FWL OF SEC 28 T 23S R 36E
 COUNTY Lea STATE New Mexico SPACING
 LOCATION (BOTTOM HOLE) Same

GEOLOGICAL ESTIMATES

<u>ZONE</u>	<u>TOP</u>	<u>THICKNESS</u>	<u>CONTENT</u>	<u>ZONE</u>	<u>TOP</u>	<u>THICKNESS</u>	<u>CON</u>
Water SS	370'	130'					
Rustler Anhy.	1480'						
Salado Salt	1600'						
Base Salt	3220'						
Yates SS	3410'		Gas				
Seven Rivers	3670'		Gas, Oil, Water				
Dolo.							
TD	3720'						

<u>CORING NO.</u>	<u>TYPE</u>	<u>HORIZON</u>	<u>INTERVAL FROM-TO</u>	<u>FOOTAGE</u>	<u>REMARKS</u>
-------------------	-------------	----------------	-------------------------	----------------	----------------

None

DRILL STEM TESTSWATER SHUT OFF TESTS

<u>NUMBER</u>	<u>HORIZON</u>	<u>NUMBER</u>	<u>HORIZON</u>	<u>NUMBER</u>	<u>HORIZON</u>	<u>NUMBER</u>	<u>HORIZON</u>
---------------	----------------	---------------	----------------	---------------	----------------	---------------	----------------

None

WELL SURVEYS (List types by code numbers as follows: Directional and/or Deviation (1) Deflection (2) Caliper (3) Temperature (4) Electrical (5) Radio active (6) Geolograph (7) Photoclinometer (8) Mudlogging (9) Other (10) and name of that type.)

<u>DEPTH POINTS</u>	<u>TYPE</u>	<u>HOLE SIZE</u>	<u>REMARKS</u>
0'-TD	(7) Geolograph	12 1/4" & 7 7/8"	
0'-TD	(2) Deflection	12 1/4" & 7 7/8"	1 every 250' to base of salt & 1 every 50' thereafter
3000'-TD	(5) DLL-GR	7 7/8"	5" & 2"
3000'-TD	(6) FDC-CNL-GR	7 7/8"	5" & 2"
1500'-TD	(3) Caliper	7 7/8"	5" & 2"
0'-TD	(4) Temperature	5 1/2" Csg.	Determine top of cement
3000'-TD	(5) GR-Collar	5 1/2" Csg.	5" Depth Control

FUEL AND WATER (SOURCE)

Contractor to furnish fuel
 Conoco to furnish water