

CENTRALIZERS & SCRATCHERS

TYPE OF STRING BY CODE LIFTERS, i.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LIFTER (L); OPERATIONS (FP)

TYPE OF STRINGS & INTERVAL (FT)		DRIFT		WT PER FT		GRADE	THREAD	AMT	WT. IN AIR, WT. IN MUD		REMARKS
FROM	TO	OD	ID	OD	PER FT				1000 LBS	1000 LBS	
0	0'-1500'	8 5/8"	7.972"	24.00		K-55	STC	1500'	36		
0	0'-3720'	5 1/2"	4.825"	15.50		K-55	STC	3720'	57.66		Sand blast bottom 400

CENTRALIZERS
INTERVAL
NO. FROM-TO

SCRATCHER
NO. INTERVAL
NO. FROM-TO

OTHER ACCESSORY EQUIPMENT
(SUCH AS DEGASSERS, MUD. CENTRIFUGE
FLOAT COLLARS, ETC. - SPECIFY)

Surface	(15)	0'-1500'	(100' Spacing)	None		Guide Shoe & Float Collar	
Production	(2)	1350-1450 (Above 8 5/8" shoe)	(33) 3220'-3720' (15' Spacing over pay zones)			Float Shoe & Float Collar	
	(13)	3220'-3720' (1 every joint over pay zone)					