

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18644

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilson 9 Federal

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Sioux Yates

11. SEC., T., E., M., OR BLE. AND
SURVEY OR AREA

Sec. 9, T26S, R36E

12. COUNTY OR PARISH 13. STATE

Lea

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR HNG Oil Company	3. ADDRESS OF OPERATOR P. O. Box 2267, Midland, Texas 79702	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1980' FEL, Sec. 9
14. PERMIT NO. Approved 2-29-80	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2944' GR		

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF: 1-24-80

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) casing test & cement job ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

4-28-80 - Spud 2:00 p.m.

4-29-80 - Set 1405 feet 8-5/8" 23#/ft. X-42 ST&C. Cemented w/600 sx HLW w/1/4#/sx flocele and 2% CaCl mixed at 12.4 ppg followed with 250 sx Cl C w/2% CaCl and 1/4#/sx flocele mixed at 14.8 ppg. Circ. 96 sacks. WOC 18 hours. pressure tested to 500 psi.

5-4-80 - Set 3650 feet of 5-1/2" 14# K-55 ST&C. Cemented w/450 sx HLW mixed at 12.4 ppg and 225 sx Cl C w/3#/sx salt and 1/4#/sx flocele mixed at 14.8 ppg. WOC. 21-3/4 hours. Pressure tested to 1000 psi.

RECEIVED

JUN 4 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty A. Gildon
Betty A. GildonTITLE Regulatory ClerkDATE 6-3-80

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side