

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. T. CO. 107
P. O. BOX 18
HODGES, NEW

5. LEASE
NM 6726
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Meyer & Associates

3. ADDRESS OF OPERATOR
306 E. Illinois, Midland, Texas 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:


TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 17 1983



- OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Report of operations to P & A:

1. 4-18-83: Pulled rods, pump and tubing. Set BP via wireline in 5 1/2" csg. at 3165'. Placed 35' cmt. on top of BP via WL dump bailer. Top cmt at 3130'.
2. Ran tbq-loaded hole with with 80 bbls. 10# brine containing 20 sx salt gel.
3. 4-19-83: Cut 5 1/2 csg with jet cutter at 2159'. Pulled and laid down 2159' of 5 1/2 csg. Ran 2 3/8 tbq. to 2207'. Spotted 50 sx class H cmt. from 2207'-2107' (inside 5 1/2 and on top of 5 1/2" stub). WOC 15 hrs overnite.
4. Ran tbq-tagged top of cmt at approximately 2100: landed tbq at 1496'. Spotted 40 sx class H cmt from 1396-1496' (below base of 8 5/8 and inside 8 5/8). Landed tbq at 75'. Spotted 20 sx Class H cmt inside 8 5/8 from surface to 75'. Removed well heads-installed DHM. Job complete 4-20-83.
5. On 4-21-83, hauled all equipment except cattleguard off location.
6. 4-22-83: Levelled reserve pit
7. 4-28-83: Ripped loc. and removed cattleguard, rebuilt fence, P&A complete.

Subsurface Safety Valve: Manu. and Type

Set @ _____ ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. B. Taylor

TITLE

Agent

DATE

May 3, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OVER

RECEIVED
NOV 18 1983
C.C.D.
HOBBS OFFICE