

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O.S.C.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
Gifford, Mitchell & Wisenbaker

3. ADDRESS OF OPERATOR
1280 Midland Nat'l Bank Bldg. Midland, Tx.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/2/80 - Set 5½" 14# K-55 casing at 3311'. Cemented with 550 sx Class C cement w/2% CaCl and 3# salt/sk, mixed at 14.8 ppg. Wait on cement 4 days.

8/6/80 - Drilled out to 3308, pressure tested pipe at 1000 psi for 30 minutes. Held OK.

RECEIVED

AUG 8 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. B. Stiff TITLE Prod. Engineer DATE 8/7/80

(This space for Federal or State office use)

APPROVED BY: TITLE: DATE:

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

AUG 13 1980

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO