

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

copy to O.E.C.

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

JUL 28 1980

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR  
Gifford, Mitchell & Wisenbaker

3. ADDRESS OF OPERATOR  
1280 Midland Nat'l Bank Twr. Midland, TX.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) spud date

5. LEASE

NM 6726

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

Undesignated

8. FARM OR LEASE NAME

Standing Bear Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Sioux Yates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T26S, R36E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2996 GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/20/80 - spud at 12:30 A.M.

7/23-24/80 - ran 8 5/8" 24# casing and set at 1445'.  
Cemented with 825 sx of Halliburton Lite weight  
cement w/2% CaCl mixed at 12.2 ppg. and  
300 sx Class C with 2% CaCl mixed at  
14.2 ppg. Cement circulated. WOC 20 hours, Pressure  
test casing 30 minutes at 500 psi. Held OK.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. B. Smith TITLE Prod. Engineer

DATE 7/25/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUL 29 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO