

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
WELL COMPLETION OR RECOMPLETION REPORT AND LOG
5-NMOCD-Hobbs 1-BWI-MLMU
1-W.A. Frnka-Tulsa 1-BB- Engr. Tech
1-R.W. Blohm-Midland 9-WIO's
1-File

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

1a. TYPE OF WELL

OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER Water Injection

b. TYPE OF COMPLETION

NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐

7. Unit Agreement Name
Myers Langlie Mattix Unit
8. Farm or Lease Name
Myers Langlie Mattix Unit

2. Name of Operator

Getty Oil Company

9. Well No.
41

3. Address of Operator

P.O. Box 730, Hobbs, New Mexico 88240

10. Field and Pool, or Wildcat
Langlie Mattix

4. Location of Well

UNIT LETTER 0 LOCATED 660 FEET FROM THE South LINE AND 1880 FEET FROM

11. County
Lea

THE East LINE OF SEC. 30 TWP. 23S RGE. 37E NMPM

12. County
Lea

15. Date Spudded	16. Date T.D. Reached	17. Date Compl. (Ready to XXXX)	18. Elevations (DF, RKB, RT, GR, etc.)	19. Elev. Casinghead
8/11/80	8/20/80	10/17/80 Inject)	3327' G.L.	--

20. Total Depth	21. Plug Back T.D.	22. If Multiple Compl., How Many	23. Intervals Drilled By	Rotary Tools	Cable Tools
3760'	3679'	--	→	0-3760'	--

24. Producing Interval(s), of this completion - Top, Bottom, Name	25. Was Directional Survey Made
3516-3656' Queen	Yes

26. Type Electric and Other Logs Run	27. Was Well Cored
McCullough-CBL-VDL-FG-CCL 3675-2500'	Yes

28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8	24#	516	11	300 SXS	Circ 100 SXS
5 1/2	15.5#	3759'	7 7/8	1200 SXS	Circ 200 SXS

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 3/8	3400'	3400'

31. Perforation Record (Interval, size and number)	32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.										
3516, 86, 90, 3600, 02, 18, 20, 23, 31, 35, 41, 48, 50, 52, 56 = 15 (.53") Holes	<table border="1"> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>3516-3556'</td> <td>3000 gals. 20% D.I. NE Acid</td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> </table>	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	3516-3556'	3000 gals. 20% D.I. NE Acid						
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED										
3516-3556'	3000 gals. 20% D.I. NE Acid										

33. PRODUCTION							
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)	
						Shut In	
Date of Test	Hours Tested	Choke Size	Prod'n. For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
			→				
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - BBL	Gas - MCF	Water - BBL	Oil Gravity - API (Corr.)	
		→					

34. Disposition of Gas (Sold, used for fuel, vented, etc.)	Test Witnessed by

35. List of Attachments

36. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNED Dele R. Crockett TITLE Area Superintendent DATE 11/26/80

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 29 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt 2754
B. Salt _____
T. Yates 2921
T. 7 Rivers 3261
T. Queen 3570
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Paddock _____
T. Blinbry _____
T. Tubb _____
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn. _____
T. Cisco (Bough C) _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Granite _____
T. Delaware Sand _____
T. Bone Springs _____
T. Rustler 1183
T. Penrose 3677

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn. "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Qtzite _____
T. Granite _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
No. 2, from _____ to _____
No. 3, from _____ to _____
No. 4, from _____ to _____
No. 5, from _____ to _____
No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1183	1183	Surface, Redbed & Sand	Core #1:			
1183	2754	1571	Anhydrite	3588	3648	60'	Recovered 59'
2754	2921	167	Salt	Core #2:			
2921	3261	340	Sand, Anhydrite	3648	3708	60'	Recovered 60'
3261	3570	309	Dolomite, Anhydrite, Sand				
3570	3677	107	Sand, Anhydrite,				
3677	3760	83	Sand & Lime				

CORE DESCRIPTIONS

Core #1 - Cut 60'; Recovered 59'.
3585-91' - very fine grained, gray Dolomitic sand stone interbedded w/silty gray Dolomite.
31-3613' - light gray fine crystalline Dolomite w/styolites and shell partings.
13-32' - interbedded very fine grained gray sand stone and gray silty Dolomite.

CONTINUED ON NEXT PAGE