

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well <input checked="" type="checkbox"/> gas well <input type="checkbox"/> other <input type="checkbox"/>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Amoco Production Company	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 68, Hobbs, New Mexico 88240	8. FARM OR LEASE NAME Federal BM
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FNL x 1980' FWL, Sec. 25 AT TOP PROD. INTERVAL: (Unit F, SE/4 NW/4) AT TOTAL DEPTH:	9. WELL NO. 1
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	10. FIELD OR WILDCAT NAME Wildcat Wolfcamp
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 25-24-32
	12. COUNTY OR PARISH Lea
	13. STATE NM
	14. API NO.
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3572.5 RDB

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 1-27-82 (X-Pert #2). Killed well with 2% KCL water. Installed BOP. Pulled packer and tubing. Ran CIBP set at 14154'. Capped with 35' of cement. Ran tailpipe, packer, and tubing. Tubing landed at 13099' and packer set at 10889'. Swabbed 1 hour and recovered 30 barrels of load water. Perforated Wolfcamp interval 13212'-13228' with 2 JSPF. Swabbed 5 hours, recovered 16 BW. Acidized with 2500 gallons 15% NEFE HCL and flushed with 74 barrels 2% KCL. Swab tested 16 hours and recovered 105 barrels of load water. Currently evaluating.

0+6-USGS, R 1-Hou 1-W. Stafford, Hou 1-DMF 1-Susp

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Freeman TITLE Ast. Adm. Analyst DATE 2-16-82

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY ROGER A. CHAPMAN

CONDITIONS OF APPROVAL, IF ANY:

FEB 26 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

